



www.CPIRoadSolutions.com (800) 428-3266

Product Data Sheet

BIOMELT® SUPREME Anti-icing/Deicing Fluid

BIOMELT® SUPREME Anti-icing/Deicing fluid is a Bioengineered agricultural product derived from renewable resources that features snow and ice control performance superior to traditional brines, but less corrosive. BIOMELT® SUPREME will reduce application rates by 30 – 50% compared to typical acetate and chloride deicers and substantially reduce operating costs while providing a sustainable and environmentally sensitive alternative.

Typical Properties

Appearance	Green semi clear	Freeze Point	-40°F (-40°C)
Dry Solids	60%	pH	6.0 – 8.5
Specific Gravity	~1.18	Water Solubility	Complete
Wt. / Gal.	~9.8 lbs/gal		

Applications

BIOMELT® SUPREME is engineered to be blended with sodium chloride brine for prewet, anti-icing, deicing applications. Optimum blended formulation is 30% BIOMELT® SUPREME plus 70% sodium chloride brine. No special blending equipment necessary. The suggested application usage levels should be considered as starting points and should be adjusted based on field operator experience, current local conditions and weather expectations.

Prewet



Apply 4–10 gals / ton (15 –38 liters / metric ton)**
Totally compatible when mixed with brines
Apply at spinner or auger
Reduce bounce and scatter loss

Truck and Employee can cover 30% more area
Increase Manpower & Equipment efficiency
Reduce application rate 30%
Reduce equipment replacement cost
Reduce Operating Cost

** Apply at recommended BIOMELT® blend ratios directly related to environmental conditions

PDSBiomeltSupreme-090920

Anti – icing



Apply before storm event to prevent Bonding
Apply at 30-35 gals / Ln mile (113-132 ltrs / kilometer)**
Residual will last 4-6 days
Reduced corrosion – contains no chlorides

Reduced application rates 30%
Truck and Employee can cover 30% more area
Commercial sidewalks 1-2 fluid oz per square yard
Reduce equipment replacement cost

** Apply at recommended BIOMELT® blend ratios directly related to environmental conditions.

Deicing



Allow product to penetrate – breaking bond to road
Apply at 60-70 gals / Ln mile (227-264 ltrs / kilometer)**
Reduce application rate 50% compared to typical KAC

Burns through hardpack to break bond with road
Totally compatible when mixed with brines
Commercial sidewalks 3-4 fluid oz per square yard

** Apply at recommended BIOMELT® blend ratios directly related to environmental conditions

The information and recommendations in this publication are to the best of sellers knowledge, accurate. However because of numerous factors affecting test results, seller makes no warranty of any kind, express or implied other than product conforms to its applicable current standard specifications. Statements concerning the use of the products or formulations described herein are not to be construed as recommending the infringement of any patent.

BIOMELT®USA

Approved 09/09/20

PDSBiomeltSupreme-090920