PRODUCT INFORMATION

DRY MOLY

AEROSOL DRY LUBRICANT

DESCRIPTION

DRY MOLY is a superior dry film lubricant, formulated with molybdenum for long lasting lubrication with anti-seize properties. **DRY MOLY** withstands high pressure, high temperatures, water and chemical attack. The dry film is ideal for use in dusty, dirty locations by avoiding dirty build-ups. **DRY MOLY** provides excellent lubrication properties without attraction of dust or dirt creating a smooth, frictionless surface for maximum operating efficiency.

USE

DRY MOLY reduces metal wear and fatigue to extend equipment life and will not break down under high temperatures. Use **DRY MOLY** on gears, chains, motors, bearings, boilers, engines, pump assemblies, conveyors, construction equipment, farm implement equipment.

DIRECTIONS

Shake well before use. Spray 8-10 inches from surface. Spray a light, even film. Wipe off excess with cloth and repeat application. A second coat provides additional protection. ALWAYS READ LABEL BEFORE USING PRODUCT.

WARNING

Keep away from heat, sparks, or open flame. Effects of overexposure include irritation of respiratory tract, headache, dizziness, nausea, and loss of coordination. Always read label before using product.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID

SKIN: Immediately flush exposed area with water for at least 15 minutes. If irritation persists, get medical attention. Remove contaminated clothing and launder before reuse. EYES: Immediately flush with large quantities of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Seek medical attention. INHALATION: Remove person to fresh air. If irritation persists, give oxygen. Get medical attention. INGESTION: DO NOT induce vomiting. Seek medical attention immediately.

Note: See Material Safety Data Sheet for Additional Precautions and First Aid Information.

Revised 11-29-23

