

PRODUCT INFORMATION

E.P. 772 GEAR OIL

DESCRIPTION

E.P. 772 Gear Oil is formulated with premium quality paraffin-based stock oils, made especially for extreme use, and heavy-duty applications. Extreme pressure additives enable **E.P. 772** to withstand the most severe shock loads while the adhesive/cohesive agents provide maximum protection for gears. Oxidation/Corrosion Inhibitors and Anti-Wear/Anti-Foam Additives complete the package for unsurpassed metal-to-metal gear protection. **E.P. 772** Gear Oil meets or exceeds MIL-L-2105 B-C.

E.P. 772 Gear Oil contains additives to reduce foam and maintain lower operating temperatures. It adheres to metal surfaces for minimal friction, wear and prevents dry starts. It maximizes protection in extreme duty conditions. Oxidation inhibitors coupled with selected paraffin base oils provide maximum protection. Cooler operating temperatures prolong oil life and provide extended drain intervals.

USE

Use **E.P. 772** Gear Oil as a service fill for axles, manual transmissions, transfer cases, power dividers, differentials, heavy-duty hypoid and spiral bevel axles, automotive and industrial worm gears and particularly on conventional axles using phosphate treated gears.

DIRECTIONS

Use **E.P. 772** Gear Oil in freshly drained gearboxes. Never mix with "SCL" lubricants. If gearboxes must be flushed before adding new fill, flush only with a solvent that will evaporate completely. **DO NOT OVERFILL** gearbox as foaming, high temperature or damage to seals may occur. With vented gearboxes, check vents to see that they are open and working properly.

DO NOT use **E.P. 772** Gear Oil for automatic transmissions or farm and industrial tractors or any equipment with combined transmission, axle and hydraulic systems. **E.P. 772** is available in single viscosity 90W and multi-viscosity SAE 85W140. The SAE weight selected for any equipment should correspond with the recommended weight and temperature recommendations in the manufacturer's manual.

WARNING

May cause an allergic skin reaction. Always read label before using product. Avoid breathing mist, vapors or spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. **KEEP OUT OF REACH OF CHILDREN.**

Note: See Material Safety Data Sheet for Additional Precautions and First Aid Information.

Revised 11-29-23

CORRELATED PRODUCTS

A division of Waverly Industries, LLC. 145 W Shore Dr. Culver, IN 46511
PHONE 317-243-3248 / TOLL FREE 1-800-428-3266

