# PRODUCT INFORMATION

# **CLION-X**

## **DESCRIPTION**

**CLION-X** effectively removes all chloride salt residues from salt spreaders, plows, vehicles, and equipment. Chloride salt residue forms a strong and corrosive bond with painted and unpainted metals. Remove all traces of chloride salt residue from your equipment to prevent rust, integrity failure, to prolong the life of your equipment and increase the return on your investment. Include **CLION-X** in your maintenance programs.

#### **DIRECTIONS**

Mix **CLION-X** with water at 8 oz. per gallon and use to wash equipment as normal. For heavy buildup of salts, mix with water at 10 oz. per gallon.

### **SPECIFICATIONS**

Color	Clear Liquid
Odor	Slight Acidic Odor
Boiling Point	221°F
Vapor Pressure (mmHg)	14.6-80
Vapor Density (AIR=1)	1.3@20°C
Solubility in Water	Complete
Specific Gravity (H <sub>2</sub> O=1)	1.05 to 1.18
· · · · · · · · · · · · · · · · · · ·	

# WARNING

This product is for Industrial and Institutional Use Only. This product contains Phosphoric Acid and Hydrofluoric Acid, which may be fatal if ingested. These inorganic acids may cause severe burns if used improperly. Avoid direct contact with skin. Wear protective clothing. Rinse empty container before disposal. Always read label before using. KEEP OUT OF THE REACH OF CHILDREN.

# **FIRST AID**

**Skin:** Immediately flush skin with cool water under shower while removing contaminated clothing and boots. Discard non-rubber shoes. wash clothing before reuse. Get immediate medical attention. **Eyes:** Flush with plenty of water for at least 15 minutes, get medical attention. **Ingestion:** Can cause severe mouth, throat and stomach burns. Can effect kidney function and be fatal if swallowed. Take immediately to a hospital or physician. **Inhalation:** remove victim to fresh air. Get medical attention if breathing is difficult.

Note: See Material Safety Data Sheet for First Aid and additional Information.

Revised 11/2023

