PRODUCT INFORMATION

SIERRA HIGH SOLIDS FLOOR FINISH

DESCRIPTION

SIERRA is a high solids, acrylic floor finish that combines high performance with "goof-proof" application. A unique combination of polish hardness and resilience produces a finish that dissipates the energy of foot traffic, providing outstanding black mark and scuff resistance. **SIERRA** provides the following performance advantages: Dries to a glossy "wet look". Longer lasting gloss, means fewer reapplications and reduced labor costs. Dry, glossy formula does not require buffing. Low ammonia odor. Makes recoating simple. Low sensitivity to humidity during application. Easily repair areas of "wear". Ease in removing black heel marks, by simply wiping or dust mopping. High resistance to powdering and dusting. Rapid drying time.

USE

SIERRA can be used on all types of composition and mineral (stone) floors. **SIERRA** produces a clean, non-yellowing acrylic coating.

DIRECTIONS

- 1. Strip floor thoroughly to remove all wax and other finishes.
- 2. Allow floor to dry completely.
- 3. Apply 2 coats of **SIERRA** floor finish, using a chenille (cotton) applicator for small areas and a clean, laundered rayon mop for large areas.
- 4. Allow 30 minutes drying time between coats.
- 5. **SIERRA** is a dry, high-gloss finish. No buffing is required.

WARNING

May be harmful if swallowed. Causes mild skin irritation. Harmful to aquatic life with long lasting effects. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID

If eye or skin contact: Wash off immediately with plenty of water. Consult a physician if needed. If inhalation: Remove to fresh air. If ingestion: Clean mouth with water and drink afterwards plenty of water.

Note: See Material Safety Data Sheet for Additional Precautions and First Aid Information.

Revised 11-29-23

