

PRODUCT INFORMATION

CORREL-LUBE 800 Bulk

DESCRIPTION	CORREL-LUBE 800 is a non-soap bentone base grease fortified with extreme pressure additives that provide a Timken OK load of 55. These extreme pressure additives allow CORREL-LUBE 800 to absorb shock loads and impact pressures yet remain extremely stable under a wide variety of conditions including moisture, acid and alkali. CORREL-LUBE 800 is a non-melt lubricant capable of operating continuously at temperatures of up to 500°F. CORREL-LUBE 800 is additionally capable of operating in excess of 500°F intermittently. CORREL-LUBE 800 contains special rust and corrosion inhibitors that provide resistance against water, steam, salt spray, oxidation and most acids. The unique combination of high viscosity index paraffinic base stocks, modifiers and improvers, coupled with an inorganic gelling agent enables CORREL-LUBE 800 to be used equally well in low or high temperatures.
USE	CORREL-LUBE 800 is recommended for indoor and outdoor lubrication of automotive, commercial transport, agricultural, industrial, construction, mining, and marine equipment.
DIRECTIONS	For best lubricating results, old grease should be removed prior to applying CORREL-LUBE 800. For grease fitting application, fill with CORREL-LUBE 800 until all old grease is forced out.
WARNING	Effects of Over Exposure: Eyes: May cause irritation. Skin: Repeated or prolonged contact may cause irritation and/or dermatitis. Ingestion: May cause gastrointestinal disturbances such as nausea, vomiting and diarrhea. KEEP OUT OF REACH OF CHILDREN.
FIRST AID	Inhalation: Move exposed person to fresh air. Get medical attention if symptoms occur. No symptoms expected. Ingestion: Wash out mouth with water. Do not induce vomiting. Get medical attention if nausea or stomach pains occur. Skin contact: Remove contaminated clothing and shoes. Wash skin with soap and water. Get medical attention if irritation symptoms occur. High pressure injection under skin requires immediate medical attention. Eye contact: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 5 minutes, keeping eyelids open. Get medical attention if redness or irritation persists.

Note: See Material Safety Data Sheet for Precautions and Additional Specifications and Information.

Revised 11/2023

CORRELATED PRODUCTS

A division of Waverly Industries, LLC. 145 W Shore Dr. Culver, IN 46511
PHONE 317-243-3248 / TOLL FREE 1-800-428-3266

